



DYNALENE

FEATURES:

- Fixed or adjustable for easy positioning
- Lightweight
- Floats
- Easy inspection without removing
- Excellent durability

DYNALENE SIZE	FITS ROPE DIAMETER*
SMALL	7/8 to 1-1/4 in.
MEDIUM	1-5/16 to 1-5/8 in.
LARGE	1-3/4 to 3 in.
EXTRA-LARGE	3-1/4 to 4 in.

**When installing over a splice area, add two sizes to your rope diameter and then select the appropriate Dynalene size.*



Great choice for mooring and offshore applications. Field repairable, rope is easily inspected without removal.

DC GARD

FEATURES:

- Fixed or adjustable for easy positioning
- Light and flexible
- Floats
- Can be removed for rope inspection
- Cut resistant
- Superior durability

DC GARD SIZE	FITS ROPE DIAMETER*
SIZE C	1 to 1-1/8 in.
SIZE D	1-1/4 to 1-3/4 in.
SIZE E	1-7/8 to 2-1/8 in.
SIZE F	2-1/4 to 2-7/8 in.
SIZE G	3 to 3-1/4 in.
SIZE H	3-5/8 to 5 in.

**Contact Customer Service to calculate size for installing over splice.*



Can be removed for rope inspection, excellent choice for tug and mooring applications

DC Gard provides maximum protection for working ropes.

SOUTHWEST OCEAN SERVICES

5718 Armour Drive
Houston, Texas 77020
1-800-231-6687
Fax: 713-671-2515

www.swos.net

