



TURBO-75

FEATURES:

- Excellent single drum spooling capabilities
- Lightweight handling
- Superior drum compression resistance
- Retains hard round shape during use
- Protective cover with Dyneema® provides superior wear characteristics

APPLICATIONS:

- Single or split drum winch primary mooring lines for various vessels
- Wire replacements in commercial fishing trawl systems
- “Tugger” winch lines for AHVs
- Deep water lifting projects
- Tractor tug winch lines
- Rig tow lines

SPECIFICATIONS:

Specific Gravity:
.98

Elastic Elongation Percentage:
At % of break strength
10% 0.33%
20% 0.49%
30% 0.76%

Size Diameter INCHES	Size Circumference INCHES	Weight Per 100 FT. POUNDS	SRT MBS* POUNDS	Size Diameter MILLIMETERS	Weight Per 100 M KILOGRAMS	SRT MBS* METRIC TONS	ISO/BS EN919 MBS METRIC TONS
1 in.	3 in.	25.0 lbs.	87,300 lbs.	24mm	37.2 Kg	39.6 MT	44.0 MT
1-1/8 in.	3-1/2 in.	29.5 lbs.	113,000 lbs.	28mm	43.9 Kg	51.0 MT	56.7 MT
1-1/4 in.	3-3/4 in.	38.5 lbs.	135,000 lbs.	30mm	57.3 Kg	61.2 MT	68.0 MT
1-3/8 in.	4-1/8 in.	48.0 lbs.	167,000 lbs.	34mm	71.4 Kg	75.5 MT	83.9 MT
1-1/2 in.	4-1/2 in.	59.5 lbs.	189,000 lbs.	36mm	88.5 Kg	85.7 MT	95.3 MT
1-5/8 in.	5 in.	67.0 lbs.	225,000 lbs.	40mm	99.7 Kg	102.0 MT	113.0 MT
1-3/4 in.	5-1/2 in.	80.5 lbs.	275,000 lbs.	44mm	120.0 Kg	125.0 MT	138.0 MT
2 in.	6 in.	93.0 lbs.	329,000 lbs.	48mm	138.0 Kg	149.0 MT	166.0 MT
2-1/8 in.	6-1/2 in.	105.0 lbs.	351,000 lbs.	52mm	156.0 Kg	159.0 MT	177.0 MT
2-1/4 in.	7 in.	120.0 lbs.	405,000 lbs.	56mm	179.0 Kg	184.0 MT	204.0 MT

*Spliced strength

SOUTHWEST OCEAN SERVICES

5718 Armour Drive
Houston, Texas 77020
1-800-231-6687
Fax: 713-671-2515

www.swos.net

