



# TURBO-EPX

## FEATURES:

- Good grip on winch drums
- Heat resistant
- Lightweight for safer and easier handling
- Superior winch performance with firm, round construction

## APPLICATIONS:

- Wire replacement – jacketed
- Deepwater lowering and lifting lines
- Primary mooring lines
- Winch based tug working lines
- Wire replacement – tug working pendant

## SPECIFICATIONS:

Specific Gravity:  
1.13

Elastic Elongation Percentage:

At % of break strength

10% 0.30%

20% 0.50%

30% 0.80%

Size Diameter INCHES	Size Circumference INCHES	Weight Per 100 FT. POUNDS	SRT MBS* POUNDS	Size Diameter MILLIMETERS	Weight Per 100 M KILOGRAMS	SRT MBS* METRIC TONS	ISO/BS EN919 MBS METRIC TONS
1 in.	3 in.	28.0 lbs.	87,300 lbs.	24mm	41.7 Kg	39.6 MT	44.0 MT
1-1/8 in.	3-1/2 in.	33.0 lbs.	113,000 lbs.	28mm	49.1 Kg	51.0 MT	56.7 MT
1-1/4 in.	3-3/4 in.	43.0 lbs.	135,000 lbs.	30mm	64.0 Kg	61.2 MT	68.0 MT
1-5/16 in.	4 in.	47.0 lbs.	149,000 lbs.	32mm	69.9 Kg	67.4 MT	74.8 MT
1-3/8 in.	4-1/8 in.	50.0 lbs.	167,000 lbs.	34mm	74.4 Kg	75.5 MT	83.9 MT
1-1/2 in.	4-1/2 in.	65.0 lbs.	189,000 lbs.	36mm	96.7 Kg	85.7 MT	95.3 MT
1-5/8 in.	5 in.	75.0 lbs.	225,000 lbs.	40mm	112.0 Kg	102.0 MT	113.0 MT
1-3/4 in.	5-1/2 in.	90.0 lbs.	275,000 lbs.	44mm	134.0 Kg	125.0 MT	138.0 MT
2 in.	6 in.	105.0 lbs.	329,000 lbs.	48mm	156.0 Kg	149.0 MT	166.0 MT
2-1/8 in.	6-1/2 in.	118.0 lbs.	351,000 lbs.	52mm	176.0 Kg	159.0 MT	177.0 MT
2-1/4 in.	7 in.	138.0 lbs.	405,000 lbs.	56mm	205.0 Kg	184.0 MT	204.0 MT

\*Spliced strength

## SOUTHWEST OCEAN SERVICES

5718 Armour Drive  
Houston, Texas 77020  
1-800-231-6687  
Fax: 713-671-2515

[www.swos.net](http://www.swos.net)

